

# DRACO BS720 FLUORESCENT



12" - 16"



Suspended Luminaire

**Application:** DRACO® BS720 compact fluorescent combines energy efficiency and Italian design. The decorative, yet durable extruded aluminum ballast housing can be suspension cable or pendant mounted. Depending on lamp type, 12" or 16" refractors can be applied. Several refractor types are available. The spun aluminum trim ring assists in the luminous performance and acts as a support for the refractor. The DRACO® BS720CF is ideal for retail stores, open ceiling areas, loft style offices, schools and residential installations.

Type: \_\_\_\_\_

Project: \_\_\_\_\_

**CONFIGURE:**

a	MODEL	b	LAMPS	c	REFRACTOR	d	MOUNTING	e	INPUT	f	OPTIONS	
BS720CF		126W	1x26W CF	142W	1x42W CF	12ACT	12" acrylic clear translucent	AC50	cable 50"	120V	CCH	custom color housing
		226W	2x26W CF	242W	2x42W CF	12ART	12" acrylic red translucent	AC72	cable 72"	277V	SPCW	spiral cord white
		326W	3x26W CF	342W	3x42W CF	12ABT	12" acrylic blue translucent	AC100	cable 100"	120/277V	SPCB	spiral cord black
		426W	4x26W CF	442W	4x42W CF	12AGT	12" acrylic green translucent	AC150	cable 150"	347V	CR	custom refractor
		132W	1x32W CF			12AAT	12" acrylic amber translucent	AC250	cable 250"		EM	650 lumens
		232W	2x32W CF			12AL	12" aluminum	PK12	pendant 12"		SL12	12" safety lens
		332W	3x32W CF			16ACT	16" acrylic clear translucent	PK18	pendant 18"		SL16	16" safety lens
		432W	4x32W CF			16AL	16" aluminum	PK24	pendant 24"			
								PK36	pendant 36"			
								PKCL	custom pendant			
												NOTE (1): EM will operate one lamp
												NOTE (2): For custom color specify color code or sample
MODEL	a	LAMPS	b	REFRACTOR	c	MOUNTING	d	INPUT	e	OPTIONS	f	
BS720CF												

**HOUSING:** Extruded aluminum construction with powder coated silver metallic as standard. Custom finishes including painting and anodizing.

**REFRACTOR:** 12" acrylic translucent prismatic design available in clear (ACT), red (ART), blue (ABT), green (AGT), and amber (AAT). Also available in spun aluminum (AL). 16" acrylic translucent prismatic design available in clear (ACT). Also available in spun aluminum (AL).

**LAMP/SOCKET:** (1-4) 26W, 32W, or 42W GX24q series base CF lamp. (lamp(s) not included).

**MOUNTING:** AC50 50" aviation cable, adjustable. AC72 72" aviation cable, adjustable. AC100 100" aviation cable, adjustable. AC150 150" aviation cable, adjustable. AC250 250" aviation cable, adjustable. Aviation cable mount uses 1/4" deep, 5" diameter white canopy. Pendant luminaires to have flat, 5" diameter white canopy. Canopies mount to standard 4" octagonal junction box supplied by others. PK12 12" pendant 3/8" IPS, PK18 18" pendant 3/8" IPS, PK24 24" pendant 3/8" IPS, PK36 36" pendant 3/8" IPS, PKCL custom pendant length, diameter and

finish. SVL swivel pendant connector has 45° rotation and 75lbs maximum load.

**POWER LINE/FEED:** 18/4 SJT straight white cord, 60" long, cord may be field cut. Power line / feed attached to housing for all mounting types.

**ALUMINUM TRIM:** Spun 1100-0 aluminum trim ring, 0.080" thickness; suspended by four (4) high polished, formed aluminum support arms.





